



A FLEXIBLE METHOD FOR PRODUCING F.E.M. ANALYSIS OF BONE USING OPEN-SOURCE SOFTWARE



Abhishektha Boppana¹, Ryan Sefcik², Dr. Jerry G. Myers³, Dr. Beth Lewandowski³

¹Case Western Reserve University, Cleveland, OH 44106 ²The Ohio State University, Columbus, OH, 43210 ³NASA Glenn Research Center, Cleveland, OH, 44135



A Graphical User

Background:

- Astronauts may lose up to 9% of loadbearing bone density per month in spaceflight¹
- Lower chance of fracture in space due to lower loads (0G)²
- Higher loads on Earth (1G) result in a higher potential for fracture due to lowered bone density when astronauts return to Earth²
- Computational bone strength model can be used to assess bone fracture risk for astronauts

Objective:


Develop and test an open-source computational bone strength model for acceptable performance in the assessment of pre-flight and post-flight astronaut bone strength studies.


Open Source Advantage:

- Publicly published with a community collaborative mindset, where others are encouraged to view and contribute to the code to advance development
- Allows for expanded future development and input from a large community of experts

Hypothesis:

Combine existing open-source software with our own scripts (Python)






Performing image segmentation through


Image Segmentation:

- Python script imports CT scans with visualization toolkit (VTK)
 - Library allows for import of many popular medical image formats
 - Script translates pixel values to Hounsfield values using metadata in original CT scans
- Script isolates bone from medical images with thresholding based on Hounsfield values
- Final image is binary representation of bone regions


3D Model Construction:


- Python's VTK toolkit includes a Marching Cubes algorithm
 - Creates a 2D surface mesh from binary segmented regions³
 - Also smooths mesh and removes unnecessary triangles
- Blender⁴ used to repair mesh and isolate any areas of interest
- 2D surface mesh was recreated into a 3D volume mesh with Gmsh⁵






Material Properties Assignment:






Skull model with dynamically applied material properties


- Original CT scans' Hounsfield values extrapolated into densities and Young's modulus using Keneko et al.'s 6 prior bone Future Work: ash testing
 - Translates Hounsfield value to bone ash density
 - Extrapolates Young's modulus from bone ash density
- Python script writes material properties to an FEBio XML file for easy import





Figures from Keneko et al. ² showing relationship between Hounsfield value, ash density, and Young's modulus


In-House Developed Interface:




process of image segmentation and 2D mesh creation into a centralized tool User can select stack of

Interface (GUI) combines

- medical images to import and can view stack in three dimensions
- Users can perform image segmentation using their inputted threshold value
- Exports a 2D mesh for next processing step in Blender and Gmsh



Graphical User Interface for tool



Contour map of effective stress (left) and pressure (right) on vertebrae model

Finite Element Analysis (FEA):

- Finite Element Analysis performed through FEBio⁷ suite
- Software allows for the graphical fixing of points, defining of loads and boundary conditions
- Allows for graphical viewing of end results

Conclusions:

- No straightforward method to implement existing open-source software into desired product
- A combination of various open source software along with self-developed scripts was needed to complete the segmentation, 3D construction, and FEA analysis tasks

- Need to design and run a selection of test cases to validate our method, including a full end-to-end simulation
- Extend further aspects of tool into interface, allowing for full integration of method into a single location

Acknowledgments:

This project was supported by the 2015 NASA Glenn Space Academy

Other Acknowledgements include:

Chris R. Werner (Zin Technologies) Ohio Space Grant Consortium

Ohio Aerospace Institute

References:

- Sibonga et al., "Recovery of spaceflight-induced bone loss: Bone mineral density after long-duration missions as fitted
- with an exponential function," Bone, Vol. 41, Issue 6, pp. 973-978, 2007. "Bones in Space", NASA For Educators [online], http://www.nasa.gov/audience/foreducators/postsecondary/features/F_Bones_in_Space.html [retrieved 12 January
- Narkbuakaew et al., "3D surface reconstruction of large medical data using marching cubes in VTK," National Electronics and Computer Technology Center, Phahon Yothin Rd, Klong Luang, Pathumthani, Thailand, May 2015.
- Blender Online Community, "Blender a 3D modelling and rendering package", Blender Foundation, http://www.blender.org, 2015.
- 5. C. Geuzaine and J.-F. Remacle, "Gmsh: A 3-D finite element mesh generator with built-in pre- and post-processing facilities," International Journal for Numerical Methods in Engineering, vol. 79, no. 11, pp. 1309-1331, 2009. 6. Keneko et al., "Mechanical properties, density and quantitative CT scan data of trabecular bone with and without
- metastases," Journal of Biomaterials, Vol. 37, Issue 4, pp. 523-530. S. Mass, B. Ellis, G. Ateshian and J. Weiss, "Finite elements for biomechanics," Journal of Biomechanical Engineering,